



EP-2225 DSL PROTECTION SPECIFICATIONS

| | | |
|-----------------------|--|---|
| | PRODUCT NUMBER | EP2225 |
| | OPERATING FREQUENCY | 0 - 10 MHz |
| | CONNECTION | RJ11 EMI/RFI filtered jacks |
| CLAMPING LEVEL | 100 V | DIMENSIONS Length: 4.438" Width: 1.25" Height: 1.063" |
| RESPONSE TIME | Approx. 1psec | |
| APPLICATION | Is acceptable for DSL & ADSL communications. | |

EP-2235 DSL PUNCH DOWN BLOCK SPECIFICATIONS

| | | | |
|-----------------------|--|----------------------------|---|
| CLAMPING LEVEL | 100 V | PRODUCT NUMBER | EP2235 |
| RESPONSE TIME | Approx. 1psec | OPERATING FREQUENCY | 0 - 10 MHz |
| APPLICATION | Analog voice telephone, DSL & ADSL communications. | DIMENSIONS | Length: 1.25" Width: .375" Height: .75" |



EP-2275 ETHERNET PROTECTION SPECIFICATIONS

| | | |
|-----------------------|---|--|
| | PRODUCT NUMBER | EP2275 |
| | OPERATING FREQUENCY | 0 - 185 MHz |
| | CONNECTION | RJ45 EMI/RFI filtered jacks |
| CLAMPING LEVEL | 13 V | DIMENSIONS Length: 4.875" Width: 1.375" Height: 1.063" |
| RESPONSE TIME | Approx. 1psec | |
| APPLICATION | Acceptable for data communications up to 100 Mbps transmission. | |

*must provide voltages and carrier frequency