



### EP-2225 DSL PROTECTION SPECIFICATIONS

	<b>PRODUCT NUMBER</b>	EP2225
	<b>OPERATING FREQUENCY</b>	0 - 10 MHz
	<b>CONNECTION</b>	RJ11 EMI/RFI filtered jacks
<b>CLAMPING LEVEL</b>	100 V	<b>DIMENSIONS</b> Length: 4.438" Width: 1.25" Height: 1.063"
<b>RESPONSE TIME</b>	Approx. 1psec	
<b>APPLICATION</b>	Is acceptable for DSL & ADSL communications.	

### EP-2235 DSL PUNCH DOWN BLOCK SPECIFICATIONS

<b>CLAMPING LEVEL</b>	100 V	<b>PRODUCT NUMBER</b>	EP2235
<b>RESPONSE TIME</b>	Approx. 1psec	<b>OPERATING FREQUENCY</b>	0 - 10 MHz
<b>APPLICATION</b>	Analog voice telephone, DSL & ADSL communications.	<b>DIMENSIONS</b>	Length: 1.25" Width: .375" Height: .75"



### EP-2275 ETHERNET PROTECTION SPECIFICATIONS

	<b>PRODUCT NUMBER</b>	EP2275
	<b>OPERATING FREQUENCY</b>	0 - 185 MHz
	<b>CONNECTION</b>	RJ45 EMI/RFI filtered jacks
<b>CLAMPING LEVEL</b>	13 V	<b>DIMENSIONS</b> Length: 4.875" Width: 1.375" Height: 1.063"
<b>RESPONSE TIME</b>	Approx. 1psec	
<b>APPLICATION</b>	Acceptable for data communications up to 100 Mbps transmission.	

\*must provide voltages and carrier frequency